



ELITE SERIES®

CSW24V

HIGH-TRAFFIC COMMERCIAL DC GATE OPERATOR WITH BATTERY BACKUP



Engineered to Work Every Time. Built to Last Over Time.

LiftMaster® Elite Series® model CSW24V is engineered for a million cycles in high-cycle heavy-duty applications. The model CSW24V is rated for gates up to 18 feet or 1200 lbs.

Battery Backup provides uninterrupted access when the power is out.

The Security+ 2.0™ technology used exclusively in LiftMaster® remote controls virtually eliminates interference and provides up to double the range of standard remotes so you do not have to wait at the gate to access your property. The receiver holds up to 50 remotes and is compatible with HomeLink® version 4 and higher.

The industry's only standard wireless dual gate communication saves installation time and cost and eliminates unsightly scars from cutting driveways to run conduit for primary/secondary communication wiring.



- **Battery Backup**
Uninterrupted access when the power is out

- **Security+ 2.0™ technology**
2X the range of standard remotes

- **MyQ™ technology provides**
 - Wireless dual gate communication
 - The ability to remotely monitor and activate your gate from anywhere in the world via internet or smart phone



LiftMaster®

Brasil #2940 Col. Desarrollo
Las Torres Valle Oriente
Monterrey N.L. C.P. 64760

ventas@puertasautomaticasdelnorte.com
(81) 83-11-16-00 Conmutador
www.puertasautomaticasdelnorte.com



Contactanos
Presupuesto sin
compromiso

CSW24V

**HIGH-TRAFFIC COMMERCIAL
DC GATE OPERATOR WITH
BATTERY BACKUP**

Specifications

- Power**
110V or 220V Single Phase
- Accessory Power**
24VDC 500mA output
Switched & Unswitched Power
- Surge**
Industrial strength suppression
on high and low voltage inputs
- Operator Duty Rating**
Continuous
- Temperature Specifications**
-40°F (-40C) to 140°F (60C)
- Gate Travel Speed**
90-degree opening in
13 – 15 seconds
- Warranty**
5 Years Commercial
7 Years Residential

Construction

- Chassis**
Constructed with ¼" gold zinc
plated steel for rust prevention
- Motor**
24VDC continuous-duty motor
- Worm Gear Reduction**
2 commercial oil bath gear boxes
with 30:1 worm gear reduction
- Cover**
High-density, UV-resistant
polycarbonate two-piece
cover for excellent heat
and corrosion resistance
- Operator Weight**
206 lbs.

Add to Your System



EL2000
Multi-Tenant Telephone Entry System



EL25 & TAC1
Single/Multi-Tenant Telephone Entry System



LOOPDETLM
LiftMaster® Plug-in Loop Detector



SOLPNL20W12V
20-Watt 12V Solar Panels



CPS UN4
Thru-Beam Photo-Eyes




G65 MGR20
Safety Edges



GHTRKITSW
Heater Kit

FOR MORE ACCESSORIES GO TO LIFTMASTER.COM

Recommended Capacities



Battery Backup Operation

BATTERY	CYCLES
2 - 7Ah	100
2 - 33Ah	380

12 ft / 800 lbs Swing Gate

Dimensions



LiftMaster®

The Chamberlain Group, Inc. • 845 Larch Avenue • Elmhurst, IL 60126
www.liftmaster.com
ISO 9001 Certified Manufacturer



©2011 LM CSW24V 12/11
The Chamberlain Group, Inc.
Printed in U.S.A.

**Brasil #2940 Col. Desarrollo
Las Torres Valle Oriente
Monterrey N.L. C.P. 64760**

ventas@puertasautomaticasdelnorte.com
(81) 83-11-16-00 Conmutador
www.puertasautomaticasdelnorte.com



**Contactanos
Presupuesto sin
compromiso**

Features/Benefits



Battery Backup

Works when the power is out. Provides up to 7 days or 100 cycles on battery backup. Powers safety devices and ancillary devices.



Security+ 2.0™ Technology

Double the range of standard transmitters. Multi frequency radio virtually eliminates interference. Receiver holds up to 50 remotes. Homelink® compatible.



Wireless Dual Gate Communication

No more unsightly driveway scars or expensive wiring.

Heavy Duty DC Motor with Soft Start/Stop Operation

Powerful enough to perform in the most demanding applications. Soft start/stop operation extends operator and hardware life under high-cycle, heavy gate use.



Fire Department Compliant

Selectable settings allow gate to auto-open upon loss of AC power or battery depletion.

Programmable Auxiliary Relays

Save time and money when adding on auxiliary devices.

2 programmable relays with 6 settings each simplify adding additional features.

- Pre-warning or gate in motion sounder
- Switch on/off devices at open or close limits

High-Impact Polycarbonate

UV-resistant 2-part cover. Offers durable protection and ease of service.



External Obstruction Sensing

Comply with UL325 safety code. To meet UL325 standards, secondary entrapment devices must be added. Inputs are provided to simplify secondary non-contact or contact sensors such as photo-eyes and edge devices. Installer will recommend best secondary entrapment device for the application.



MyQ™ Enabled Accessories

LiftMaster's revolutionary MyQ™ technology is designed with simple mobile access control in mind. The new LiftMaster® model CSW24V comes with MyQ™ technology built-in. Pair it with our LiftMaster Internet Gateway™ accessory to remotely monitor or open or close your gate from anywhere in the world with one click on your Internet-enabled computer or smart phone.



Exceptional Standby Time

Our battery backup lasts for days.

10 seconds after the gate closes, all non-essential ancillary devices turn off to conserve power.



True Power Management System


Protects Battery Life. Recovers batteries quicker when discharged and manages the low power threshold. Will not run the batteries beyond the point of failure, ensuring batteries are ready for the next time they are needed.



Simple-to-Set

Electronic Limit System

Maintains accurate gate position throughout gate travel. Maintains open and close limit position at all times, even after using manual disconnect.



Bi-Part Delay

Selectable dual gate operation

Standard Operation – Simultaneously closes gates at the same time.

Synchronized close – Monitors the speed and position of each wing and adjusts the speed as necessary to ensure primary gate closes last, avoiding potential damage to the gate.



Plug-in Loop Detectors

Easy to install, simple to program.

Features 8 different settings, including boost. Innovative technology eliminates crosstalk. Inputs for shadow, interrupt and exit loops.



Advanced Traffic

Management Control

Discourages tailgating

Quick Close – Closes the gate immediately after a vehicle pulls off the interrupt loop.

Anti-Tailgate – Prevents unauthorized access. Gate will pause when closing as vehicle pulls onto interrupt loop or breaks photo beam. Once vehicle backs up, gate will continue to close.



LiftMaster Internet Gateway™

(model 828LM)

LiftMaster's revolutionary new accessory features built-in MyQ™ technology that connects to the Internet and allows you to monitor and operate your gate operator from anywhere in the world via your internet-enabled computer or smart phone.



Garage and Gate Monitor

(model 829LM)

Lets you check and close the gate operator from any room in your house.



Remote Light Control

(model 825LM)

Control your house lights and operate any lamp with your remote control or from your Internet-enabled smart phone via your LiftMaster Internet Gateway™

LiftMaster Internet Gateway™ Accessory functionality is dependent on communication with MyQ™ enabled gate operator. MyQ™ communication can be limited by distance and exterior building materials. A general range estimate is 300 feet.



LiftMaster®

Brasil #2940 Col. Desarrollo
Las Torres Valle Oriente
Monterrey N.L. C.P. 64760

ventas@puertasautomaticasdelnorte.com
(81) 83-11-16-00 Conmutador
www.puertasautomaticasdelnorte.com



Contactanos
Presupuesto sin
compromiso